

R.M.H. Horizontal Mixer Trailers

Australian Standard specifications only.

Every attempt has been made to accurately describe and price components. However we reserve the right to alter prices and descriptions without notice as well as reserves the right to make changes in the design, or to add improvements to the products, without incurring an obligation on goods purchased.

Models 420 & 490

Standard Specifications:-

3 CR 12 Stainless Steel bottom.
Discharge door made from 3 CR 12 stainless steel.
Hydraulically operated discharge door.
4 hydraulic hoses for quick tractor connection.
Medium discharge conveyor (hydraulically driven)
Flanged augers with heavy-duty tubes.
Flanged hubs with removable high strength shafts.
2 NC (non continuous) bottom augers with knives.
2 continuous top augers, with knives, rotating in the same direction.
Planetary gear with heavy-duty roller chain drives in an oil bath.
Heavy-duty bearings on drive auger shafts.
P.T.O. drive shaft with shear bolt.
2 position heavy-duty rotating clevis hitch.
Mechanical Jack, Trailer Ladder & Battery box.
2 Remoulded tyres (aviation type) 44.5 x 16.5 x 20 & 8 holed rims.
R.M.H. Electronic weighing system with 1 indicator & 4 weigh-bars 1% accuracy

Optional Equipment:- (Most Optional Equipment must be ordered as standard fitment ex factory)

Long Discharge conveyor
2 Electric hydraulic valves for discharge door and conveyor
Magnets on discharge door (short fingers)
R.M.H. remote weighing display
R.M.H. remote weighing display with radio control
(Note:- when this is ordered a different indicator is supplied)
Perfect Feed computerised scale (50 rations, with 30 items each)
Power Feed computerised scale
Spare wheel 44.5 x 16.5 x 20
Hydraulic brakes
Fully swinging Elevator for discharge into self feeders
Machine fitted roller mills to suit customers requirements

R.M.H Horizontal Mixer Trailers

Models 580 (6.5 Ton Cap) & 630 (8.5 Ton Cap)

580 Standard Specifications:-

3 CR 12 Stainless steel bottoms and discharge door.
Hydraulically operated discharge door and medium conveyor.
4 hydraulic hoses for quick tractor connection.
Flanged augers with heavy-duty tubes.
Flanged hubs with removable high strength shafts.
2 NC (non continuous) bottom augers with knives.
2 continuous top augers, with knives, rotating in the opposite direction.
Planetary gear (13.2 reduction) with heavy-duty roller chain drives in an oil bath.
Heavy-duty bearings on drive auger shafts.
P.T.O. drive shaft with shear bolt.
2 position heavy-duty rotating clevis hitch.
Mechanical Jack, Trailer ladder & Battery box.
2 remoulded tyres (aviation type) on 10 holed rims.
R.M.H. Electronic weighing system with 1 indicator & 4 weigh-bars 1% accuracy.
<u>630 Standard Specification same as 580 Spec plus the following:-</u>
Heavy-duty axle 110mm, Strengthened chassis and bin on the bottom of the tank

Optional Equipment:- (Most Optional Equipment must be ordered as standard fittment ex factory)

Long discharge conveyor
2 Electric hydraulic valves for discharge door and conveyor
Magnets on discharge door (short fingers)
R.M.H. remote weighing display
R.M.H. remote weighing display with radio control
(Note:- when this is ordered a different indicator is supplied)
Perfect Feed computerised scale (50 rations,with 30 items each)
Power Feed computerised scale
Spare Wheel
Hydraulic brakes
Fully swinging elevator for discharge into self feeders
Machine fitted roller mills to suit customers requirements