

# R.M.H. Horizontal Mixers – Truck Mount

## Australian Standard specifications only.

Every attempt has been made to accurately describe and price components. However we reserve the right to alter prices and descriptions without notice as well as reserves the right to make changes in the design, or to add improvements to the products, without incurring an obligation on goods purchased.

### Models 580T/M ( 7 Ton Cap ) – 630T/M ( 10Ton Cap )

#### 580T/M Standard Specifications:-

3 CR 12 Stainless steel bottoms and discharge door.
Electrical hydraulical system for discharge door and for medium discharge conveyor.
Flanged augers with heavy-duty tubes.
Flanged hubs with removable high strength shafts.
2 NC (non continuous) bottom augers with knives.
2 Continuous top augers, with knives, rotating in opposite directions.
Planetary gear (13.2 reduction) with heavy-duty roller chain drives in an oil bath.
Heavy-duty bearings on drive auger shafts.
Danfoss OMVS 400 hydraulic motor coupled to gear-box (Reggianna)
Solenoids and valve blocks as required for hydraulic installation.
Truck chassis mounting frame (mounted on the truck chassis and to the bin`s 4 corners via
R.M.H. Electronic weighing system with 1 indicator & 4 weigh-bars 1% accuracy.
R.M.H. remote weighing display.

#### Optional Equipment. - (Most Optional Equipment must be ordered as standard fittment ex factory)

2 Continuous bottom augers with knives (for feedlots mainly) in lieu of standard NC augers
Magnets on discharge door (short fingers)
Perfect Feed computerised scale (50 rations, with 30 items each)

**Important!!!** When ordering a Truck Mount we must have the location of the discharge door and the direction of rotation of the augers.