

R.M.H. Vertical Mixer Trailers

Australian Standard specifications only.

Every attempt has been made to accurately describe and price components. However we reserve the right to alter prices and descriptions without notice as well as reserves the right to make changes in the design, or to add improvements to the products, without incurring an obligation on goods purchased.

Model WAV-8

Standard Specification:-

One vertical auger.
Heavy Duty vertical planetary gears, integrated with 90 degrees bevel gears
Single speed
High quality chrome vanadium parabolic steel blades (Tungsten on first 4 bottom
2 Contra knives.
Hydraulically operated discharge door.
Viewing platform.
P.T.O. drive shaft with shear bolt.
2 X Wheels 10.0/75R-15.3 18 PR.
Adjustable heavy duty rotating homologated drawbar.
Mechanical jack.
Long tilting conveyor (1.4 m) operated by 3 electrical hyd. valves: control from tractor cab.
Top circular protecting tube.
R.M.H Electronic weighing system with: One Indicator Simple Feed 21 & 3 weigh bars 1% Accuracy

Model WAV-12E

Standard Specification:-

One vertical auger.
Heavy Duty vertical planetary gears, integrated with 90 degrees bevel gears
Single speed
High quality chrome vanadium parabolic steel blades (Tungsten on first 4 bottom blades).
Contra knife - manual control
Long tilting conveyer (1.4 m) RH discharge, operated by 3 electrical valves:
Viewing platform.
2 Wheels: 10.0 x 75R - 15.3 18 PLY.
Adjustable heavy duty rotating homologated drawbar.
R.M.H Electronic weighing system with: One Indicator Simple Feed 21 & 3 weigh bars 1% Accuracy
Top circular protecting tube.
Mechanical jack.

Model WAV-14

Standard Specification:-

One vertical auger.
Heavy Duty vertical planetary Gear, integrated with 90 degrees bevel gear.
100 HP two speed gearbox
High quality chrome vanadium parabolic steel blades (Tungsten on first 4 bottom blades).
2 Contra knives.
Hydraulically operated discharge door.
Viewing platform.
P.T.O. drive shaft with shear bolt.
2 X Wheels 28 x 12.5 x 15 (24 PLY RATING)
Adjustable heavy duty rotating homologated drawbar.
Mechanical jack.
RMH Electronic weighing system with: One indicator Simple Feed 21 & 3 weigh bars 1% Accuracy.
Long tilting conveyor (1.4 m) operated by 3 electrical hyd. Valves: control from tractor cab.
Transmission sys. for changing gear speed - controlled from tractor cab (push-pull cable).
Top circular protecting tube.

Model WAV-16

Standard Specification:-

One vertical auger.
Heavy Duty vertical planetary Gear, integrated with 90 degrees bevel gear.
100 HP two speed gearbox
High quality chrome vanadium parabolic steel blades (Tungsten on first 4 bottom blades).
2 Contra knives.
Hydraulically operated discharge door.
Viewing platform.
P.T.O. drive shaft with shear bolt.
2 X Wheels 28 x 12.5 x 15 (24 PLY RATING)
Adjustable heavy duty rotating homologated drawbar.
Mechanical jack.
RMH Electronic weighing system with: One indicator Simple Feed 21 & 3 weigh bars 1% Accuracy.
Long tilting conveyor (1.4 m) operated by 3 electrical hyd. Valves: control from tractor cab.
Transmission sys. for changing gear speed - controlled from tractor cab (push-pull cable).
Top circular protecting tube.

Models VR18

Standard Specification:-

Two vertical augers.
Two heavy Duty vertical planetary Gears, one with through shaft, both integrated with 90 degrees bevel gear.
125 HP two speed gearbox
Transmission sys. for changing gear speed - controlled from tractor cab (push-pull cable).
High quality chrome vanadium parabolic steel blades (Tungsten on first 4 bottom blades on each auger).
4 Contra knives.
Hydraulically operated discharge door.
2 side hydraulically operated front mounted discharge conveyor with chain & slats (cross conveyor)
4 Hydraulic hoses with quick hydraulic connection.
Viewing platform.
P.T.O. shaft with shear bolt.
2 Remoulded tyres and rims 10 holes (aviation tyres) 44.5 x 16.5 x 20.
Adjustable heavy duty rotating homologated drawbar.
Mechanical jack.
R.M.H Electronic weighing system with: One Indicator Simple Feed 21 & 4 weigh bars 1% Accuracy
Additional Remote display for Simple feed 21 with radio control zeroing button
Top circular protecting tube.

Model VR26

Standard Specifications:-

Two vertical augers.
Two Heavy Duty vertical planetary Gears, one with through shaft, both integrated with 90 degrees bevel gear.
125 H.P. two speed gearbox
High quality chrome vanadium parabolic steel blades (Tungsten on first 4 bottom blades on each auger).
4 Contra knives.
Hydraulically operated dual discharge door.
Viewing platform.
P.T.O. drive shaft with shear bolt.
4 x WHEELS 28 x 12.5 x 15 (24 PLY).
Adjustable heavy duty rotating homologated drawbar.
Two axles with leaves spring cantilever suspension.
Mechanical jack.
Hydraulic brakes.
1.4m long tilting chain & slat conveyors for both RH and LH discharge, operated by electrical valves: controlled from tractor cab.
Transmission sys. For changing gear speed - controlled from tractor cab (push-pull cable).
Top circular protecting tube.
R.M.H Electronic weighing system with: One Indicator Simple Feed 21 & 4 weigh bars 1% Accuracy
Additional Remote display for Simple feed 21 with radio control zeroing button